

SEMICONDUCTOR CAPACITORS HAVING TANTALUM OXIDE LAYERS AND METHODS FOR MANUFACTURING THE SAME

Cross-Reference to Related Applications

The present application claims priority to Korean Patent Application No. 01-3165 filed January 19, 2001, the disclosure of which is incorporated herein by reference in its entirety.

5

Field of the Invention

The present invention generally relates to semiconductor capacitors, methods of making semiconductor capacitors, as well as microelectronic devices comprising semiconductor capacitors.

10

Background of the Invention

As the integration density of semiconductor devices increases, the employment of dielectric layers having relatively high dielectric constants is desirable for potentially securing high capacitance in relatively small areas.

15

One representative example of a dielectric layer having a relatively high dielectric constant is a tantalum oxide (Ta_2O_5) layer.

20

Notwithstanding its relatively high dielectric constant, the use of the tantalum oxide layer is potentially problematic in that it typically is potentially highly reactive with polysilicon present as a lower electrode in a conventional capacitor. In particular, polysilicon is usually oxidized in the formation of a tantalum oxide layer or a thermal treatment process after the formation of a tantalum oxide layer.

In an attempt to address this problem, lower electrodes have been formed from materials which are believed to be relatively difficult to oxidize.


Examples of such materials include noble metals such as platinum (Pt), ruthenium (Ru), or iridium (Ir), or a conductive metal nitride layer such as titanium nitride (TiN). However, the use of a noble metal or metal nitride also presents potential problems. A conventional tantalum oxide layer is typically formed by chemical vapor deposition in an oxygen atmosphere using pentaethoxide tantalum (PET), $\text{Ta}(\text{OCH}_3)_5$, or TaCl_5 as a tantalum source. Oxygen (O_2), water (H_2O), hydrogen peroxide (H_2O_2), or nitrous oxide (N_2O) is employed as an oxygen source in such a method. Notwithstanding any advantages associated therewith, a composition of these source gases often negatively impacts the coverage of the tantalum oxide layer, presumably due to the oxidation of the lower electrode. For example, when a ruthenium (Ru) layer is used as a lower electrode, the surface of the Ru layer is oxidized by an oxygen source which results in the formation of RuO_2 .

The formation of RuO_2 is carried out so as to minimize or prevent the formation of a tantalum oxide layer. The formation of a tantalum oxide layer often occurs when such a layer is used as a dielectric layer in a cylindrical or concave-shaped capacitor having a large aspect ratio. In such an instance, the tantalum oxide layer is not deposited on the lower portion of the cylindrical opening in the Ru electrode. Instead, the tantalum oxide layer is typically deposited on the upper portion to deteriorate step coverage of this layer.

There is a need in the art to address the above-mentioned problems in the art. More specifically, there is a need in the art to provide a semiconductor capacitor having a tantalum oxide layer present thereon with a more uniform thickness. It would be desirable to obtain a capacitor having a relatively high aspect ratio.


Summary of the Invention

In one aspect, the invention provides semiconductor capacitors comprising first electrodes, second electrodes, and tantalum oxide layers positioned between the first electrodes and the second electrodes. The tantalum oxide layers are formed by depositing at least one precursor and ozone gas, with the precursor represented by the formula:



5 wherein X is selected from the group consisting of nitrogen, sulfur, oxygen, and a carbonyl group, and R₁ and R₂ are independently alkyl (e.g., C₁ to C₄ alkyl).

10 In another aspect, the invention provides methods of making semiconductor capacitors. The methods comprise forming first electrodes on semiconductor substrates, and then forming tantalum oxide layers on the first electrodes by depositing at least one precursor and ozone gas. The at least one precursor is represented by the formula:



20 wherein X is selected from the group consisting of nitrogen, sulfur, oxygen, and a carbonyl group; and R₁ and R₂ may be independently alkyl; and

forming second electrodes on the tantalum oxide layers.

These and other aspects and advantages of the present invention are

described herein.

5

Brief Description of the Drawings

FIG. 1 illustrates a cylindrical capacitor formed according to a preferred embodiment of the present invention.

FIGS. 2A and 2B schematically illustrate sections of prior art substrates wherein tantalum oxide layers are formed using H_2O and O_2 respectively, as oxygen sources.


FIG. 3 is a graph illustrating equilibrium vapor pressure with respect to temperature of PET and TAT-DMAE precursors according to the present invention.

FIG. 4 typically illustrates an adsorption mechanism of gaseous tantalum precursors on an Ru lower electrode according to the present invention.

Detailed Description of the Invention

The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. In the drawings, the thicknesses of layers and regions are exaggerated for clarity. Like numbers refer to like elements throughout. It will also be understood that when a layer is referred to as being "on" another layer or substrate, it can be directly on the other layer or substrate, or intervening layers may also be present.

In one aspect, the invention provides semiconductor capacitors. The semiconductor capacitors comprise first electrodes, second electrodes, and tantalum oxide layers positioned between the first electrodes and the second electrodes. The tantalum oxide layers are formed from by depositing at least one precursor and ozone gas on the first electrode. The precursor is represented by the formula:



wherein X is selected from the group consisting of nitrogen, sulfur, oxygen, and a carbonyl group; and

R₁ and R₂ are independently alkyl (e.g., C₁ to C₄ alkyl).


In one preferred embodiment, R₁ and R₂ are each methyl and X is nitrogen.

The tantalum oxide layer may be formed by various techniques. In one embodiment, for example, the tantalum oxide layer may be formed by depositing the precursor and a source gas on the first substrate. The source gas is preferably present as ozone gas.

Various materials can be employed in the first electrode of the invention. Examples of such materials can include, without limitation, a polysilicon, a noble metal, a conductive metal nitride, and combinations thereof. Exemplary noble metals include, without limitation, Ru, Ir, Pt, and combinations thereof. Exemplary conductive metal nitrides include, without limitation, TiN, TaN, WN, and combinations thereof. These same materials may also be included, without limitation, in the second electrode of the invention.

As described in detail, the tantalum oxide may be deposited using various conditions. In one preferred embodiment, the tantalum oxide layer is deposited at a temperature ranging from about 100°C to about 600°C.

In another aspect, the invention provides methods of making semiconductor capacitors. The methods comprise forming a first electrodes on semiconductor substrates, forming tantalum oxide layers on the first electrodes by depositing at least one precursor and ozone gas thereon. The precursor is represented by the formula:



5

wherein X is selected from the group consisting of nitrogen, sulfur, oxygen, and a carbonyl group; and R₁ and R₂ are independently alkyl including, for example, C₁ to C₄ alkyl, and forming a second electrode on the tantalum oxide layer.

10

The methods of the invention may be carried out according to various preferred embodiments, although it will be appreciated that these embodiments are non-limiting and that the invention may be practiced by employment of other embodiments. In one embodiment, the step of forming tantalum oxide layers on the first electrodes injecting the one or more precursors, ozone gas and a purge gas on the first electrode sequentially. In another embodiment, the methods further comprise the step of forming a tantalum preprocessed layer on the surface of the first electrode by depositing at least one tantalum precursor including an oxygen bond by chemical vapor deposition prior to the step of forming a tantalum oxide layer on the first electrode. Examples of the one or more tantalum precursors include, without limitation, Ta(OC₂H₅)₅, Ta(OCH₃)₅, and combinations thereof.

15

20

Examples of purge gas that may be used in the methods of the invention include, without limitation, argon, nitrogen, or mixtures thereof.

25

The methods of the invention can be carried out under various processing conditions. In one embodiment, for example, the step of depositing one or more precursors on the first electrode occurs at a temperature ranging from about 100°C to about 600°C.


30

The present invention will now be illustrated more fully with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. It should be appreciated that the embodiments

presented in the drawings are for illustrative purposes only, and do not limit the scope of the present invention.

FIG. 1 illustrates an example of a structure of a capacitor formed according to the present invention. In this embodiment, the capacitor is cylindrical, although it should be appreciated that the capacitor may be formed as other geometrics. Referring to **FIG. 1**, the capacitor has a structure in which a TEOS layer **100** having a cylindrical opening, a lower electrode **110**, a tantalum oxide layer **120** and an upper electrode **130** are sequentially deposited along the TEOS layer **100**. The lower electrode can be formed of polysilicon, a noble metal such as Ru, Pt, Ir, or combinations thereof, and a conductive metal nitride layer such as TiN, TaN, WN, or combinations thereof. In addition to employment of a single metal nitride layer, a solid solution nitride layer such as, for example, (Ti, Ta)N can be used as the upper electrode, along with other materials. Also, a composite layer formed by depositing at least two materials described above can be used.

In one embodiment according to the present invention, the tantalum oxide layer may be formed by chemical vapor deposition using tantalum precursors of a monomer expressed by Formula A and ozone as a source gas.



A

wherein X has a coordination bond with Ta formed through an unshared electron pair. It is preferable that X is N, S, O, or C=O. R₁ and R₂ are independently selected as an alkyl group such as, for example, preferably a C₁ to C₄ alkyl group. In a preferred embodiment, R₁ and R₂ are each methyl groups.

In this embodiment, ozone is used as an oxygen source for depositing the tantalum oxide layer of the present invention. The ozone gas can be used

as an oxidizer for forming a tantalum oxide layer at a temperature below, for example, 400°C, in contrast to the thermal conditions employed using O₂, H₂O or N₂O as gases. It should be appreciated that other temperature conditions can be employed.

5 The chemical vapor deposition method can be performed, for example, by general thermal chemical vapor deposition or atomic layer deposition techniques, as well as other techniques. According to the thermal chemical vapor deposition method, tantalum precursors and ozone gas simultaneously flow into a deposition chamber. Conversely, tantalum precursors and ozone gas sequentially flow into a deposition chamber to deposit a tantalum oxide layer in an atomic layer deposition method.

10 One example of an atomic layer deposition method of the present invention may be carried out as follows. It should be appreciated that variations from this method can occur with departure from the scope of the invention. First, a semiconductor substrate is introduced into a deposition chamber. A lower electrode **110** is present thereon. Next, tantalum precursors expressed by Formula A are introduced into the deposition chamber, and the tantalum precursors are chemically or physically adsorbed on the surface of an Ru electrode **110** of the semiconductor substrate. The
15 tantalum precursors are typically provided by a bubbling method or a liquid delivery system (LDS) method. After the adsorption is complete and a predetermined time has elapsed, nitrogen, or an inert purge gas such as argon, is introduced into the deposition chamber to preferably remove the remaining tantalum precursors from the deposition chamber, with the
20 exception of the adsorbed tantalum precursors. After a predetermined time has elapsed, the inflow of the purge gas is stopped, and ozone gas is introduced into the deposition chamber. The ozone gas is believed to react with the adsorbed tantalum precursors to form a tantalum oxide layer. After the inside of the deposition chamber is purged with nitrogen or inert gas such as argon, a cycle of: (1) inflow of tantalum precursors, then (2) inflow of purge gas, then (3) inflow of ozone gas, and then (4) inflow of purge gas is carried out repeatedly to form a tantalum oxide layer **120** having a desired thickness.

25 During the deposition, it is preferable that the flow rate of the tantalum precursors range from about 1 to about 2000 sccm. Nitrogen or argon is preferably employed as the purge gas, and the flow rate preferably ranges from about 1 to about 2000 sccm. The ozone gas flow rate preferably ranges from about 1 to about 2000 sccm. The temperature of the deposition chamber preferably ranges from 100°C to about 600°C, and the pressure of
30

the deposition chamber preferably ranges from about 0.1 Torr to about 30 Torr.

After formation of the lower electrode **110** and before formation of the tantalum oxide layer **120**, a process for forming a tantalum preprocessed layer (not shown) can be additionally performed by repeating the inflow and purging of the tantalum precursors expressed by Formula A. This sequence can result in the simplification of the formation of the tantalum oxide layer. In such an embodiment, a thin tantalum oxide layer is formed on the lower electrode with the tantalum precursors. The tantalum oxide layer is advantageous in that it helps to minimize or prevent oxidation of the lower electrode in an oxygen atmosphere to form a tantalum oxide layer having superior step coverage.

An upper electrode **130** is formed on a dielectric layer **120**, the dielectric layer being fabricated as set forth above. The upper electrode can be formed of polysilicon, a noble metal such as Ru, Pt, Ir or combinations thereof, or a nitride layer such as TiN, TaN, WN, or combinations thereof. It should be appreciated that other materials can also be employed as well. Naturally, in addition to a single metal nitride layer being used as the upper electrode, a solid solution nitride layer such as (Ti, Ta)N can be used as the upper electrode. Also, a composite layer may be formed by depositing at least two of the materials described above.

The invention will now be described in greater detail in reference to the examples. It should be understood that the examples merely illustrate the invention and are not intended to limit the scope of the invention as defined by the claims.

Example 1

A tantalum dielectric layer was formed on a cylindrical Ru lower electrode having an aspect ratio of about 15 using tetraethoxy tantalum dimethylamino-ethoxide (TAT-DMAE) as tantalum precursors and O₃ gas as an oxygen source. The dielectric layer was formed by an atomic layer deposition method having a cycle of inflow of tantalum precursors -> purging -> inflow of O₃ -> purging. In this example, the temperature of the chamber was maintained at 250°C, 300°C, 350°C and 400°C. The thickness of the upper portion of a tantalum oxide layer deposited at each temperature (t₁ of FIG. 1) and the thickness of the lower portion of the tantalum oxide layer (t₂ of FIG. 1) were measured. Results are set forth in Table 1.

Table 1

Classification	250°C	300°C	350°C	400°C
t_1 (Å)	240	103	233	244
t_2 (Å)	220	102	207	228

As shown in Table 1, the thicknesses of the deposited layers vary with temperature. Notwithstanding these differences, it was observed that the
5 tantalum oxide layers were generally are uniform in thickness in their respective upper portions and lower portions.

Comparative Example 1

For comparison with the present invention, a tantalum oxide layer was
10 formed by an atomic layer deposition method at a temperature of 350°C using PET as a tantalum precursor, and H₂O and O₂ gases as oxygen sources, respectively. **FIGS. 2A** and **2B** schematically illustrate sections of the substrate when tantalum oxide layers are formed using the above-mentioned source gases. When H₂O was employed as the oxygen source gas, the
15 tantalum oxide layer **120** was formed on the upper portion of an opening **140**, but the tantalum oxide layer **120** was not formed on the lower portion of the opening **140** as illustrated in **FIG. 2A**. It is believed that the formation of the tantalum oxide layer **120** was prevented because of the presence of RuO₂, **110'**, formed by surface oxidation of the Ru layer **110** in the lower portion of
20 the opening. As shown in **FIG. 2B**, when the O₂ is employed as the oxygen source gas, the presence of the tantalum oxide layer was disuniform over opening **140**.

Comparative Example 2

25 Tantalum oxide layers were formed by an atomic layer deposition method at temperatures of 250°C, 300°C, 350°C and 400°C using PET as a tantalum precursor and O₃ as the oxygen source.

This example illustrates similar behavior to Comparative Example 1 which employed H₂O as the oxygen source gas. Referring to **FIG. 2A**, the
30 tantalum oxide layer **120** was formed on the upper portion of the cylindrical opening **140** at each temperature. The tantalum oxide layer was not formed on the lower portion. As the deposition temperature was increased, the depth to which the tantalum oxide layer **120** was formed (designated as **h** in **FIG. 2A**) tended to increase. **Table 2** illustrates the thicknesses (designated as **t₁**
35 and **t₂** in **FIG. 1**) of the upper portion and lower portion of the tantalum oxide

layers **120** formed at 300°C and 350°C, and also the depth to which the tantalum oxide layer **120** was formed (designated as **h** in **FIG. 2A**).

Table 2

Classification	300°C	350°C
t_1 (Å)	549	456
t_2 (Å)	~0	~0
h (Å)	3000	6700

5

Although not intending to be bound by theory, one possible reason as to why tantalum precursors of the present invention expressed by Formula A display superior coverage to other tantalum precursors, such as for example PET, will be described with respect to steric hindrance believed to be attributable to equilibrium vapor pressure and sticking probability impacting the tantalum precursor molecular structure.

10

FIG. 3 illustrates equilibrium vapor pressure with respect to temperatures of PET and TAT-DMAE. As shown, the equilibrium vapor pressure of TAT-DMAE is higher than that of PET. Therefore, at the same temperature, the equilibrium vapor pressure of TAT-DMAE is generally much higher than that of PET over the temperature range. In accordance with an embodiment of the present invention, since a tantalum precursor source gas is provided at 140°C with respect to PET and at 120°C with respect to TAT-DMAE, the equilibrium vapor pressure of TAT-DMAE is observed to be about twice as great as that of PET. A high equilibrium vapor pressure indicates that there are a greater number of gaseous molecules relative to a system having a lower equilibrium vapor pressure. With respect to a TAT-DMAE system, the amount of tantalum source gas provided into the deposition chamber is relatively sizeable. Accordingly, the number of molecules directly provided to the lower portion of the cylindrical opening is believed to be relatively large. Therefore, TAT-DMAE employed as precursors in accordance with the present invention can form a tantalum oxide layer exhibiting superior coverage to conventional PET.

15

20


25

30


Not intending to be bound by theory, it is believed that the discrepancies in vapor pressures can be attributed to a steric effect. According to Bradley, "Metal Alkoxides as Precursors for Electronic and Ceramic Materials" American Chemical Society, Chem. Rev., (1989), small alkoxides have a greater tendency to form oligomers such as dimers, trimers by bridging alkoxides groups than alkoxides of greater steric bulk. This

discrepancy is believed to exert a sizeable influence on alkoxide vapor pressure.

Accordingly, since an oxygen atom present in PET has a tendency to increase its coordination number by forming a covalent bond with a neighboring tantalum atom, the PET is likely to have the following molecular structure in a liquid state (see Formula B).



Conversely, with respect to a TAT-DMAE embodiment, because a nitrogen atom, which has a covalent bond with oxygen, has a coordination bond with a Ta atom, the TAT-DMAE exists as a monomer in a liquid state and can be expressed by the following structural formula (Formula C).



Accordingly, and although not intending to be bound by theory, it is believed that since PET has a higher thermal stability than the TAT-DMAE precursors of the present invention, the PET requires a greater level of much energy to break a bond between molecules to be volatilized and thus has a lower vapor pressure.

Another factor which potentially influences precursor coverage relates to sticking probability. According to Kawahara, "Conformal Step Coverage of (Ba, Sr)TiO₃ Films Prepared by Liquid Source CVD Using Ti(t-BuO)₂(DPM)₂", Japanese Journal of Applied Physics, Vol. 38, pp. 2205-2209, when Ti(t-BuO)₂(DPM)₂ precursors are used, (Ba, Sr)TiO₃ thin film has superior step coverage relative to embodiments which employ Ti(DPM)₂ precursors. Because the sticking probability of the Ti(t-BuO)₂(DPM)₂ referenced by Kawahara is estimated to be about 0.02, and the sticking probability of the Ti(DPM)₂ is estimated to be about 0.1, a thin film having superior coverage can be obtained when the sticking probability is low.

~~According to Si-woo Lee et al., "Chemical Vapor Deposition Precursors for (Ba, Sr)TiO₃ Films", 6th Korean Semiconductor Seminar, the deposition of Ti may be carried out using the surface reaction as a rate determining step, and high coverage may be achieved by virtue of the surface movement of Ti.~~

In view of all potential factors, and although not intending to be bound by theory, it is believed that Ti precursors possessing low sticking probability are particularly desirable suitable for making a thin film having high coverage, presumably due to relative ease of surface movement. With respect to precursor steric hindrance, since generally small precursors have a higher sticking probability than bulky precursors, the TAT-DMAE precursors may have a lower sticking probability than PET. Although not intending to be bound by theory, this may explain the superior coverage of TAT-DMAE.

FIG. 4 depicts an embodiment illustrating an adsorption mechanism of gaseous tantalum precursors on an Ru lower electrode **110** according to the present invention. Not intending to be bound by theory, the mechanism in which the tantalum precursors reach the lower portion of the opening formed by the Ru lower electrode **110** is believed to be attributable to: (a) surface movement (1) from the upper portion of the opening **140** or (b) direct transmission (2) to the lower portion of the opening **140**. Accordingly, as illustrated in **FIGS. 2A** or **3**, to minimize or prevent oxidation of Ru in the lower portion of the Ru lower electrode **110**, the provided tantalum precursors should preferably be uniformly adsorbed, and preferably cover the entire lower electrode **110** by surface diffusion or direct transmission. In order to carry out this procedure in optimal fashion, surface movement of the

precursors adsorbed on the substrate should preferably be unencumbered, and the vapor pressure should be sufficiently high to accommodate a plurality of precursors. In particular, precursors such as TAT-DMAE of the present invention typically possess a higher vapor pressure relative to conventional

5 precursors such as PET.

According to the present invention, it is possible to form a semiconductor capacitor having a tantalum oxide layer which exhibits superior coverage to a conventional layer by using tantalum precursors having an atom or an atomic group which has a coordination bond with a tantalum atom.

10 The present invention has been described in detail with respect to the preferred embodiments in the specification set forth hereinabove. It should be understood that these embodiments are intended to illustrate the invention and are not meant to limit the scope of the invention as defined by the claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192